

SECTION (feet)	HOLE #	Azimuth (degrees)	Dip (degrees)	TotalDepth (feet)	From (feet)	To (feet)	Interval (ft,m)	Gold (oz/ton)	Gold (g/t)	Silver (oz/ton)	Silver (g/t)	Gold Equiv. (oz/ton) 60Ag=1Au
400N	NP-0810	70	-45	800	320	350	30,9.1	0.028	0.959	0.17	5.8	0.031
					360	370	10,3.6	0.015	0.514	0.10	3.4	0.017
					455	465	10,3.6	0.017	0.582	0.11	3.8	0.019
	NP-0811	70	-90	740	440	475	35,12.5	0.010	0.342	0.32	11.0	0.015
600N	NP-0812	70	-90	400	80	150	70,21.3	0.012	0.411	0.16	5.5	0.015
					165	190	35,12.5	0.010	0.342	0.67	22.9	0.021
800N	NP-0809	70	-90	440	325	375	50,15.2	0.016	0.548	0.19	6.5	0.018
					400	440	40,12.2	0.021	0.719	0.58	19.9	0.031
						NP-0809A	70	-90	700	350	380	30,9.1
					395	450	55,16.8	0.009	0.308	0.29	9.9	0.014
					500	510	10,3.6	0.007	0.240	0.25	8.6	0.011
					530	570	40,12.2	0.008	0.274	0.30	10.3	0.013
1100N	NP-0807	70	-60	400	20	70	50,15.2	0.010	0.342	0.16	5.5	0.012
					100	125	25,7.6	0.010	0.342	0.09	3.1	0.012
					135	160	25,7.6	0.007	0.240	0.36	12.3	0.013
	NP-0824C	70	-45	200	18	96.5	78.5,23.9	0.015	0.514	0.18	6.2	0.018
					105.5	128	22.5,6.9	0.016	0.548	0.10	3.4	0.017
					143	161	18,5.5	0.004	0.137	0.45	15.4	0.011
1200N	NP-0813	70	-90	600	370	530	160,48.8	0.053	1.815	0.17	5.8	0.058
					Including	375	380	5,1.5	0.893	30.582	0.16	5.5
1300N	NP-0808	70	-45	395	95	165	70,21.3	0.016	0.548	0.37	12.7	0.023
					200	220	20,6.1	0.010	0.342	0.15	5.1	0.012
1700N	NP-0805	70	-60	500	155	165	10,3.6	0.011	0.377	0.12	4.1	0.013
					190	210	20,6.1	0.008	0.274	0.16	5.5	0.011
					240	290	50,15.2	0.011	0.377	0.17	5.8	0.014
1800N	NP-0825C	70	-45	210	80	180	100,32.8	0.056	1.918	0.22	7.5	0.060
					192.5	204	11.5,3.5	0.015	0.514	0.13	4.5	0.017
2200N	NP-0804	70	-45	300	70	80	10,3.6	0.025	0.856	0.33	11.3	0.030
					90	100	10,3.6	0.036	1.233	0.14	4.8	0.038
	NP-0814	70	-90	600	No Significant Values							
2400N	NP-0801	70	-45	500	320	375	55,16.8	0.010	0.342	0.41	14.0	0.017
					280	290	10,3.6	0.018	0.616	0.12	4.1	0.020
					300	335	35,12.5	0.015	0.514	0.72	24.7	0.026
					345	395	50,15.2	0.019	0.651	0.26	8.9	0.024
	NP-0803	70	-90	600	335	425	90,27.4	0.030	1.027	0.31	10.6	0.035
					460	505	45,13.7	0.010	0.342	0.11	3.8	0.012
2600N	NP-0815	70	-70	600	220	240	20,6.1	0.013	0.445	0.05	1.7	0.014
					310	330	20,6.1	0.011	0.377	0.11	3.8	0.013
					360	370	10,3.6	0.039	1.336	0.05	1.7	0.040
3000N	NP-0816	70	-90	500	240	260	20,6.1	0.013	0.445	0.10	3.4	0.014
					270	280	10,3.6	0.013	0.445	<.01	<0.5	0.013
					320	340	20,6.1	0.023	0.788	0.36	12.3	0.029
3200N	NP-0817	70	-70	600	180	190	10,3.6	0.015	0.514	0.08	2.7	0.016
					200	220	20,6.1	0.009	0.308	0.05	1.7	0.010
					285	360	75,22.9	0.048	1.644	0.11	3.8	0.050
				Including	300	310	10,3.6	0.251	8.596	0.12	4.1	0.253
	NP-0818	70	-90	600	220	250	30,9.1	0.013	0.445	0.04	1.4	0.013
					350	360	10,3.6	0.013	0.445	0.02	0.7	0.013
					370	380	10,3.6	0.021	0.719	0.08	2.7	0.022
3400N	NP-0819	70	-90	200	35	65	30,9.1	0.018	0.616	0.07	2.4	0.020
					70	100	30,9.1	0.019	0.651	0.09	3.1	0.020
					110	120	10,3.1	0.010	0.342	0.06	2.1	0.011
	NP-0820	70	-90	300	190	280	90,27.4	0.039	1.336	0.28	9.6	0.044
NP-0822	70	-90	680	290	340	50,15.2	0.013	0.445	0.03	1.0	0.014	
				620	640	20,6.1	0.016	0.548	0.12	4.1	0.018	
				650	675	25,7.6	0.013	0.445	0.59	20.2	0.023	
	NP-0827C	70	-65	555	258	345	87,26.5	0.018	0.616	0.04	1.4	0.018
					450	507.7	57.7,17.6	0.042	1.438	0.40	13.7	0.049
					510	530	20,6.1	0.032	1.096	5.05	172.9	0.116
				Including	520	525	5,1.5	0.093	3.185	8.82	302.1	0.240
3500N	NP-0823	70	-90	400	20	40	20,6.1	0.011	0.377	0.08	2.7	0.012
					90	100	10,3.1	0.012	0.411	0.05	1.7	0.013
					130	140	10,3.1	0.015	0.514	0.20	6.8	0.018
					260	270	10,3.1	0.013	0.445	0.03	1.0	0.014
					280	350	70,21.3	0.037	1.267	0.22	7.5	0.040

Note: Intervals are true thickness except -65 to -70° holes are 80% true thickness, -90° holes are 70% true thickness ;
Hole numbers missing from sequence were not drilled.